



## 2025 COYOTE RULES

- The rules and/or regulations set forth herein provide for the orderly conduct of racing events and to establish minimum acceptable requirements of such events. These rules govern the condition of all such events. All participants are deemed to have complied with these rules. No expressed or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. Rules are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant.
- Speedway Officials shall be empowered to permit minor deviations from any of the specifications herein or impose any further restrictions that in his/her opinion does not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications.
- Speedway reserves the right to update, modify, and/or delete rules at any time deemed necessary to ensure safety, fair competition or any other reason that may be appropriate. All Discussions with officials must be conducted in a professional manor.
- Cars, parts and or equipment will not be considered as having been approved by having passed through inspection at any time or number of times unobserved or undetected.
- Any interpretation or deviation of these rules is left to the officials. Any decision of and by Speedway Officials is final.
- Unsportsmanlike-like conduct can carry a minimum \$100.00 fine and/or suspension. Any and all fines will be added to the point's fund at the end of the racing season.

***Please remember If it does not say you can do it, you cannot.*** Some things you will be able to call and get permission to run. If this happens it is advisable for you to have this in writing and signed and dated from a Tech Official.

### CARS / ENGINE / TRANSMISSION:

1. American or Foreign made stock cars Front Wheel Drive only
2. No high-performance models, turbo, supercharged cars, NOS, or other performance enhancing devices will be permitted.
3. Exhaust must be stock for make and model car.
4. Engine must be stock only and No aftermarket cams.
5. Door hinges, locks, and side impact bar must remain in door and doors must be securely fastened shut.

6. Must remove all glass. If using a glass windshield must wear goggles or face shield. May use screen or Lexan – must be completely across windshield area.
7. May remove back seat, carpet, headliner, and trim panels.
8. Engine must have been available for make and model of auto claimed.
9. Engine may be a newer version of engine for claimed auto but must be same "L" Liter. (Example: You may use a 3100 for a 3.1L.
10. ECM may only be flashed once then tamper tape will be added. ECM must be stock for the make and model.
11. Plug wires: Optional 7 mm or 8 mm
12. Must run stock ignition coils- modules, chips, etc. (NO MSD)
13. Weight must be added for anything over 190HP. Weight/HP ratio is 1lb/HP. (Example: 205HP must add 15 lbs.)
14. Weight must be mounted in the center of the passenger side where seat was previously mounted.
15. Transmission must have been available for make, model and year of auto "claimed." NO MIS-MATCH OF ENGINE & TRANSMISSION
16. 4 cylinder- Automatic or Standard or 6 cylinder- Automatic

### TIRES:

1. 175-225-65, 70, 75 ... 14" or 15". NO Tire Speed rating over an "H" rated.
2. Front wheel drive will have a maximum 7-inch width. Racing wheels must run 1-inch steel lugnuts.
  - a. 4-inch minimum backsparing on left side.
  - b. 2-inch minimum backsparing right side.
  - c. Stock wheels with 2" spacer
3. Stock suspension only, no modifications. 1-inch sway bar link difference will be permitted. Stock springs and one bump stop per strut only. Maximum length 3-inches.
4. Maximum front camber is 2-inches measured at the rim.
5. May run a maximum of 2-inch spacer on right side only.

### SAFETY:

1. 5-point roll cage will be mandatory.
2. Racing seat with a 5-point harness will be mandatory and both must be mounted to the roll cage.
3. Must cover all holes in front and rear firewall and floorboard.
4. Fuel Cell or Gas Tank permitted but fuel cell must be centered in rear of the car and no lower than the frame.
5. For safety purposes must use grade 5 or stronger bolts with lock nuts to mount weight.
6. No antifreeze allowed- \$50.00 fine.

